



PVC TILES CLEANING INSTRUCTIONS

TRAFICLINE tiles are a solid and non porous floor covering, To improve ease of maintenance and also help maintain hygiene, a patented UV cured treatment is applied to the top surface.

A test report is available N°RE 03 -071 « *comparative study of dirtying and of aptitude to cleaning* » issued by the CSTB (available for download on www.traficline.com)

Regular and light cleaning is recommended rather than infrequent heavy cleaning.

FOR WEEKLY OR DAILY CLEANING : Use CLEANLINE®

- Alkaline non-foaming de-greaser, compliant with the new European environmental rules.
- Particularly effective on very dirty surfaces and on tyres marks.
- Bio-degradable: to recommended concentration, CLEANLINE is harmless on treated surfaces.
- Can be used in the food industry : compliant with the ministerial order dated 8th September 1999 (can be used for the cleaning of the material in contact with food products)
- Solvent-free, contributing to the longevity of the cleaning materials.

APPLICATION :

CLEANLINE can be applied by spraying and then cleaned using either a hand mop (e.g. Biomop), a single rotary brush, or for best results a rotary scrubber dryer.

With a single rotary brush:



- Spray the cleaning solution on the floor.
- Allow to stand for 1 or 2 minutes before scrubbing with the single rotary brush machine (nylon hard hair)
- Rinse thoroughly
- Remove excess water with a vacuum system

With a rotary scrubber dryer :



- Pour the right dose in the tank of the machine so as to have a 5% dilution with water
- Spray the cleaning solution on the floor with the machine (without vacuum on)
- Wait for 1 or 2 minutes and then go over the floor again with the scrubbing machine with the vacuum on.

NB : Choice of brushes :

For the regular maintenance of TRAFICLINE® with a single rotary brush machine or a rotary scrubber dryer, it is recommended to use nylon brushes with hard hair.

It is also possible to use « green » discs or even « brown » discs according to cases ; keep the more abrasive « black » discs for sanding operations.

Dilution :

- Dilution of 2 to 15% in water, depending on the level of grease to be removed
- Common dilution : 5% in water

Technical data and Safety data sheets to be downloaded on our website www.traficline.com.

