

Technical Data	Standard
Product	-
Thickness	mm
Dimension	cm
Colors	-
Weight in kg	par dalle
	par m <sup>2</sup>
Slip resistance	DIN51130
Surface	-
Hardness	ISO 868
Material	PVC
Fire Rating	EN 13501-1
TVOC	Airconfort Gold Blue angel
Surface Treatment	Stainproof
Mechanical resistance	E-cahier CSTB N°3562
Chemical resistance	
Dimensional stability	NF EN 434
Wear resistance	NF EN 660-1
Residual Indentation	NF EN 443
Rolling wear resistance	XPP11-101 :2001
Shifting resistance	E-cahier CSTB N° 3562
Electrical resistance	Résistance en Ohm (Ω)

TRAFICFLOOR	
100 % Blank PVC	
7	5
50 x 50	
10	
2.37	1.7
9.49	6.8
R 10	
Textured	
91.8 Shore D	
100 % Blank	
Cfl-S2	Bfl-S1
VOC A+	
STAINPROOF Option	
P/M : 4.2.1.4	
P/C : 3.3.3.2.3.0.0.3.3	
0.03 %	
P	
0.04	0.03
< 1	
> 50	> 45
Between 10 <sup>12</sup> and 10 <sup>14</sup>	

TRAFICFLOOR <span style="background-color: #4CAF50; color: white; padding: 2px;">ECO</span>	
100 % Recycled PVC	
7	5
50 x 50	
2	
2.37	1.7
9.49	6.8
R 10	
Textured	
88 Shore A	
100 % Recycled	
Bfl-S1	
VOC A+	
STAINPROOF Option	-
-	
-	
-	
P	
0.19	0.07
< 1	
> 50	> 45
Between 10 <sup>12</sup> and 10 <sup>14</sup>	

TRAFICFLOOR <span style="background-color: #FFC107; color: white; padding: 2px;">AS</span>	
100 % Blank PVC	
7	5
50 x 50	
1	
2.37	1.7
9.49	6.8
R 10	
Textured	
91.8 Shore D	
100 % Blank	
Bfl-S1	
VOC A+	
-	
-	
-	
P	
0.19	0.07
< 1	
> 50	> 45
Between 10 <sup>6</sup> and 10 <sup>12</sup>	

TRAFICFLOOR <span style="background-color: #FFEB3B; color: white; padding: 2px;">ESD</span>	
100 % Blank PVC	
7	5
50 x 50	
2	
2.37	1.7
9.49	6.8
R 10	
Textured	
91.8 Shore D	
100 % Blank	
Bfl-S1	
VOC A+	
-	
-	
-	
P	
0.19	0.07
< 1	
> 50	> 45
Between 10 <sup>4</sup> and 10 <sup>6</sup>	

TRAFICFLOOR <span style="border: 1px solid black; padding: 2px;">Extreme cold</span>	
100 % Blank PVC	
7	5
50 x 50	
1	
2.37	1.7
9.49	6.8
R 10	
Textured	
91.8 Shore D	
100 % Blank	
Bfl-S1	
VOC A+	
STAINPROOF Option	
-	
-	
-	
P	
0.19	0.07
< 1	
> 50	> 45
Between 10 <sup>12</sup> and 10 <sup>14</sup>	